

**This Page Is Inserted by IFW Operations  
and is not a part of the Official Record**

## **BEST AVAILABLE IMAGES**

**Defective images within this document are accurate representations of the original documents submitted by the applicant.**

**Defects in the images may include (but are not limited to):**

- **BLACK BORDERS**
  - **TEXT CUT OFF AT TOP, BOTTOM OR SIDES**
  - **FADED TEXT**
  - **ILLEGIBLE TEXT**
  - **SKEWED/SLANTED IMAGES**
  - **COLORED PHOTOS**
  - **BLACK OR VERY BLACK AND WHITE DARK PHOTOS**
- 
- **GRAY SCALE DOCUMENTS**

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**



**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

In re Applicant:

Yossi Berger

Serial No.: 09/708,641

Filed: November 9, 2000

For: ELECTRO-OPTICAL, OUT-DOOR  
BATTLE-FIELD SIMULATOR BASED  
ON IMAGE PROCESSING

Examiner:

Commissioner of Patents and Trademarks  
Washington, D.C. 20231

Group Art Unit: 2123

Attorney  
Docket: 26/351

RECEIVED

JUN 6 2001

TRANSMITTAL LETTER

**Technology Center 2100**

Sir:

The following documents are enclosed:

1. Certified Copy IL 132997;
2. Certified Copy IL 138097.

Respectfully submitted,

Mark M. Friedman  
Attorney for Applicant  
Registration No. 33,883

Date: May 31, 2001

2123  
#2  
V.24  
6-20



מדינת ישראל  
STATE OF ISRAEL

Ministry of Justice  
Patent Office

משרד המשפטים  
לשכת הפטנטים

RECEIVED

JUN 6 2001

Technology Center 2100

This is to certify that annexed  
hereto is a true copy of the  
documents as originally  
deposited with the patent  
application of which  
particulars are specified on the  
first page of the annex.

זאת לתעודה כי רצופים  
בזה העתקים נכונים של  
המסמכים שהופקדו  
לכתחילה עם הבקשה  
לפטנט לפי הפרטים  
הרשומים בעמוד הראשון  
של הנספח.

This 21-01-2001 היום

מ. ל. ש.  
ממונה על ה  
הפטנטים

Commissioner of Patents

נתאשר  
Certified

מספר: Number	132997
תאריך: Date	17-11-1999
הוקדם/נדחה Ante/Post-dated	

ב ק ש ה ל פ ט נ ט  
Application For Patent

אני, (שם המבקש, מענו ולגבי גוף מאוגד - מקום התאגדותו)  
I (Name and address of applicant, and in case of body corporate - place of incorporation)

State Of Israel - Ministry Of Defense  
RAFAEL - Armament Development Authority  
P.O.Box 2250  
Haifa 31021

מדינת ישראל - משרד הבטחון  
רפא"ל - רשות פתוח אמצעי לחימה  
ת.ד. 2250  
חיפה 31021

ממציא: יוסי ברגר

Inventor: Yossi Berger

בעל אמצאה מכח הדין ..... Operation of Law .....  
Owner, by virtue of .....  
of an invention the title of which is

מאמן שדה אלקטרו אופטי למערכות נשק נ"ט

(בעברית)  
(Hebrew)

ELECTRO OPTICAL FIELD SIMULATOR FOR ANTI TANK SYSTEMS

(באנגלית)  
(English)

hereby apply for a patent to be granted to me in respect thereof

מבקש בזאת כי ינתן לי עליה פטנט

• בקשת חלוקה - Application of Division	• בקשת פטנט מוסף - Application for Patent Addition	• דרישת דין קדימה Priority Claim		
מבקשת פטנט from Application	לבקשה/לפטנט to Patent/Appl.	מספר/סימן Number/Mark	תאריך Date	מדינת האיגוד Convention Country
No. .... dated .....	No. .... dated .....			
יפוי כח : כללי P.O.A.: general/individual-attached/to be filed later- הוגש בענין 109841 filed in case .....				
המען למסירת מכתבים בישראל Address for service in Israel DR. MARK FRIEDMAN LTD. BEIT SAMUELOFF 7 HAOMANIM STREET 67897 TEL AVIV				
חתימת המבקש Signature of Applicant		היום 17 בחודש Nov שנת 1999 of the year of This		
		לשימוש הלשכה For Office Use		

Ref.: 26/290

מאמן שדה אלקטרו אופטי למערכות נשק נ"ט

**ELECTRO OPTICAL FIELD SIMULATOR FOR ANTI TANK SYSTEMS**

### מאמן שדה אלקטרו אופטי למערכות נשק נ"ט

מנגנון לסגירת חוג בין טיל תרגול ומטרה לפגיעה לצורך אימון שדה למערכות נ"ט אלקטרו-אופטיות (מחליף MILES המבוסס על מנגנון לזירה).

העיקרון : קריאת תדר מזוהה של הבהוב פנס IR הנמצא על המטרה, באמצעות עיבוד תמונה (תמונת רב"ת).

בציור שלהלן מודגם העיקרון ע"פ השלבים הבאים :


1. באמצעות ראש הביות של טיל תרגול נרכשת מטרה והמפעיל נועל עליה.
2. מרגע זה משודר באמצעות משדר אלחוטי סיגנל לכל המטרות. סיגנל זה מפעיל פנס IR שנמצא על כל אחת מהמטרות. כל פנס מהבהב בתדר שונה המזוהה עם המטרה הספציפית שעליה הוא מוצב.
3. מנגנון עיבוד התמונה מזהה את תדר ההבהוב של הפנס ומשווה את התדר המזוהה עם רשימת תדרים של המטרות.
4. עם זיהוי המטרה, משודר ע"י המשדר סיגנל להפעלת מטעני פירוטכניקה על המטרה, לדימוי פגיעה.
5. מידע על המשגר היורה והמטרה שנפגעה ישודר למרכז הסימולציה לצורך עדכון נתונים.
6. סימולצית זמני מעוף וסיכויי פגיעה תשולב במערכת לצורך דימוי טיל אלקטרו אופטי מנוהג.

WHAT IS CLAIMED IS:

1. A method for simulating an attack on one of a plurality of targets, comprising the steps of:
  - (a) providing a simulated weapon that is aimable at the targets;
  - (b) for each target, generating a respective signal using an incoherent light source;
  - (c) acquiring at least one image that includes at least one of the targets; and
  - (d) inferring, from said at least one image, whether said simulated weapon is aimed at one of the targets.
2. The method of claim 1, further comprising the step of:
  - (e) if said simulated weapon is aimed at one of the targets, indicating said one target whereat said simulated weapon is aimed.

DR. MADAN LAL LTD.  
PATENT  
SAMOOR  
7 HAD  
57337

A BATTLEFIELD SIMULATOR FOR EO ATMS







מדינת ישראל  
STATE OF ISRAEL

Ministry of Justice  
Patent Office

משרד המשפטים  
לשכת הפטנטים

This is to certify that annexed  
hereto is a true copy of the  
documents as originally  
deposited with the patent  
application of which  
particulars are specified on the  
first page of the annex.

זאת לתעודה כי רצופים  
בזה העתקים נכונים של  
המסמכים שהופקדו  
לכתחילה עם הבקשה  
לפטנט לפי הפרטים  
הרשומים בעמוד הראשון  
של הנספח.

This 25-02-2007 היום

רשם הפטנטים

Commissioner of Patents

נתאשר  
Certified

ב ק ש ה ל פ ט נ ט  
Application For Patent

מספר: Number	138095
תאריך: Date	25-08-08
הוקדם/נדרחה Ante/Post-dated	

אני, (שם המבקש, מענו ולגבי גוף מאוגד - מקום התאגדותו)  
I (Name and address of applicant, and in case of body corporate - place of incorporation)

State Of Israel - Ministry Of Defense  
Rafael - Armament Development Authority  
P.O.Box 2250  
Haifa 31021

מדינת ישראל - משרד הבטחון  
רפא"ל - רשות לפתוח אמצעי לחימה  
ת.ד. 2250  
חיפה 31021

Inventor: Yosef Berger

ממציא: יוסף ברגר

בעל אמצאה מכח הדין ..... Operation of Law .....  
Owner, by virtue of  
of an invention the title of which is

סימולטור שדה-קרב אלקטרו-אופטי לשימוש בשטח  
המבוסס על עיבוד דמות


(בעברית)  
(Hebrew)

ELECTRO-OPTICAL, OUT-DOOR BATTLE-FIELD  
SIMULATOR BASED ON IMAGE PROCESSING

(באנגלית)  
(English)

hereby apply for a patent to be granted to me in respect thereof

מבקש בזאת כי ינתן לי עליה פטנט

• בקשת חלוקה - Application of Division	• בקשת פטנט מוסף - Application for Patent Addition	• דרישת דין קרימה Priority Claim		
מבקשת פטנט from Application	לבקשה/לפטנט to Patent/Appl.	מספר/סימן Number/Mark	תאריך Date	מדינת האיגוד Convention Country
No. .... dated .....	No. .... dated .....			
יפוי כח : כללי P.O.A.: general/individual-attached/to be filed later-				
הוגש בענין 109841 filed in case .....				
המען למסירת מכתבים בישראל Address for service in Israel DR. MARK FRIEDMAN LTD. BEIT SAMUELOFF 7 HAOMANIM STREET 67897 TEL AVIV				
חתימת המבקש Signature of Applicant		היום 22 בחודש Aug שנת 2000 of the year of This		
		לשימוש הלשכה For Office Use		

Ref.: 26/307

**סימולטור שדה-קרב אלקטרו-אופטי לשימוש בשטח  
המבוסס על עיבוד דמות**

**ELECTRO-OPTICAL, OUT-DOOR BATTLE-FIELD  
SIMULATOR BASED ON IMAGE PROCESSING**

# APPLICATION FOR PATENT

Inventor: Yosef Berger

## ELECTRO-OPTICAL, OUT-DOOR BATTLE-FIELD SIMULATOR 5 BASED ON IMAGE PROCESSING

### Field and Background of the Invention

The present invention relates to a military training system for firing a weapon at a target and, more particularly, to a training system for firing an electro-optically guided anti-tank missile.

#### *Simulation in training*

10 Military training exercises use simulation, wherever possible, rather than live ammunition or actual firing of weapons, both to save costs and to avoid unnecessary use of dangerous equipment.

More realistic simulation lends greater verisimilitude and helps train soldiers in conditions that more closely resemble battlefield conditions. Thus, in firing exercises, a soldier needs to aim  
15 a weapon, pull a trigger or otherwise activate firing, and see the results of a "hit".

A further requirement is that a training control center be able to monitor all training activities, if possible, in real time.

To heighten the sense of reality, there is a need for battlefield simulation systems that are integrated with armament systems and not intrusive add-ons.

#### 20 *Currently Available Simulation of Weapon Systems*

Current weapons firing simulation systems employ a laser installed on the weapon that makes it possible to simulate firing, using a laser pulse instead of ammunition, and to identify the target hit.

In the case of anti-tank missile systems (ATMS), current simulations employ a pulsed laser, which is attached to and aligned with the missile launcher and which is fired instead of a missile. Detectors placed on the target are illuminated by the laser, may record a hit, and can relay that information both to the operator of the missile and to the training control center. This method is used in, for example, the Swedish BT46 system from Saab Training Systems.

The same system can also be attached to various types of guns and artillery and operated similarly.

This is a suitable approach for rigid, so-called “stiff-neck” weapons, whose aiming is restricted to the direction of a sensor fixed relative to the missile, but not for the new generation of ATMS which feature “flexible neck” seekers, whose sensors have an overall wider field of view obtained by varying the sensor orientation relative to the missile’s canister axis. The problem here is that there is not necessarily any connection between the line of sight of the launcher and that of the seeker head.

Drawbacks of current simulation systems include:

- Rigid laser alignment:

Being attached rigidly outside the missile or gun barrel, the laser mimics the launcher operation but not that of the separate target seeker, which is located in the seeker head of the missile and operates independently of the launcher before and after firing. A sensor in the seeker head is mounted on gimbals and can alter its pitch and yaw with respect to missile orientation and the target position, as required, in order to lock onto a desired target, something the launcher-mounted laser is unable to do.

The situation may be likened to a light on a miner’s helmet that may not necessarily be illuminating the spot where the miner is actually looking. Thus, a laser “hit” is not necessarily indicative of a missile hit; nor does a laser “miss” necessarily indicate a missile miss.

- The laser apparatus is a relatively heavy and cumbersome add-on. It requires calibration before use and is not easy to use.
- The laser apparatus is hazardous to human eyesight.
- The laser apparatus is limited by adverse weather conditions.

Thus there is a recognized need for, and it would be highly advantageous to have, a training system that is better integrated with and better simulates the missile’s target-seeking operation,

itself, and that is safer, less intrusive and cumbersome, and less adversely affected by weather conditions.

## Summary of the Invention

According to the present invention there is provided a simulator for simulating the firing of a weapon at one of a plurality of targets, each target having a respective shape, including: a housing substantially identical in size and shape to at least a discrete portion of the weapon; a  
5 sensor, operationally connected to the housing, for acquiring a plurality of images of at least one of the targets; and an image processor for detecting and analyzing changes among the images and for initiating control signals based on the analysis.

According to further features of the invention described below there is included: for each target, an infra-red lamp that is alternatively activated by one of the control signals to flash at a unique,  
10 respective frequency and deactivated by another of the control signals; and a mechanism for transmitting the control signals to the lamps.

According to a preferred embodiment of the present invention, the transmitting mechanism is wireless.

According to another preferred embodiment of the present invention, the transmitting mechanism  
15 is wired.

According to a preferred embodiment of the present invention, the sensor includes a CCD television camera.

According to further features in preferred embodiments of the invention, the sensor forms part of the guidance system of an electro-optically guided missile.

20 According to further features of the present invention, there is provided a look-up table for the image processor including data about shapes of the targets and a capability of the image processor to utilize the data to calculate accuracy of aim at a target.

According to further features in preferred embodiments of the invention, there is provided, at each target, a pyrotechnic charge that is detonatable by a respective control signal and that is able  
25 to release variable quantities of smoke in accordance with the calculated accuracy of aim

According to the present invention, there is provided a method for identifying an acquired target comprising the steps of: (a) providing a weapon simulator including a housing substantially identical in size and shape to at least a discrete portion of the weapon; a sensor, operationally connected to the housing, for acquiring a plurality of images of a target; an image processor for  
30 detecting and analyzing changes among these images and for initiating control signals based on

the analysis; for each target, an infra-red lamp that is alternatively activated by one of the control signals to flash at a unique, respective frequency and deactivated by another of the control signals; and a mechanism for transmitting the control signals to the lamps; (b) aiming the housing at one of the targets; (c) transmitting a signal to activate all the infra-red lamps;  
5 (d) acquiring the plurality of images, at known time intervals, of the target aimed at; (e) passing the images to the image processor; (f) calculating the flash frequency of the lamp on the target aimed at by comparing successive images from the sensor; and (g) identifying the target aimed at by comparing the frequency with a look-up table of the unique frequencies.

10 According to further features of the present invention there is provided a method for determining accuracy of aim.

According to further features of the present invention there is provided a method for determining accuracy of aim comprising the further steps of providing a target-shape look-up table that includes data about the shapes of the respective targets and comparing the sensor images of an acquired target with the shape data.

15 According to a preferred embodiment of the present invention there is provided a method for a visual simulation of a hit.

According to a preferred embodiment of the present invention there is provided a method for a visual simulation of a hit comprising the steps of providing, at each target, a pyrotechnic charge and detonating the charge at an identified target.

20 According to preferred embodiment of the present invention there is provided a method for visually simulating the accuracy of a hit comprising the further step of differentially detonating the charge.

According to another embodiment of the present invention there is provided a method for simulation of firing of ballistic weapons.

25 According to another embodiment of the present invention there is provided a method for simulation of firing of ballistic weapons. comprising the further step of providing calculation algorithms for the image processor that include calculation of parabolic trajectories incorporating known muzzle velocities, angle of elevation, and range of said target.



## **Brief Description of the Drawings**

The invention is herein described, by way of example only, with reference to the accompanying drawings, wherein:

5           Figure 1 shows a configuration for battlefield training for electro-optically guided anti-tank missile systems;

Figure 2 is a schematic representation of the guided missile's seeker head, showing the essential components of the present invention; and

Figure 3 shows an implementation for non-electro-optically guided weapons.

# Description of the Preferred Embodiments

## *Introduction*

The present invention is of an outdoors military training system for firing a weapon at a target, which provides for interaction between the training weapon and the target. Specifically, the present invention can be used for field training for electro-optically guided anti-tank missile systems. The present invention incorporates reporting mechanisms so that a training control center can be instantly aware of the results of training exercises. The present invention is a substitute for, or additional to, the currently used BT46 system, which is based on laser mechanisms.

10 The present invention may also be adapted to field training for other types of guns and artillery.

The present invention utilizes the in-built target seeking mechanism of ATMS, with the addition of a light-weight, inexpensive, and unobtrusive image processor.

15 According to the present invention, operation relies on identification of the frequency of a flashing infra-red lamp located on an acquired target. Identification is done by means of the image processor fed by the seeker sensor, such as a television camera in the missile's own target-seeker head, or by an add-on sensor.

The principles and operation of the present invention may be better understood with reference to the drawings and the accompanying description.

## *Configuration and operation*

20 In general, the simulated weapon is a housing that represents, in shape and size, a discrete portion of a real weapon, and sufficient of the launcher to enable training in aiming and firing. It includes a missile guidance system but neither propulsion system nor explosive charge. Figure 1 shows a schematic view of the present invention in operation, for the case of an ATMS, and Figure 2 a block diagram of the relevant parts of the missile's seeker head and the image processor.

25 The electro-optical guidance system of a missile simulator 10 includes a sensor 20, such as a CCD television camera or imager, in the seeker head 11 thereof. In practice, the missile simulator could be an actual missile, less the propulsion system and explosive charge thereof.

In normal use, sensor 20, which is sensitive to infra-red and visible light, captures an image 26 of a target 12. Sensor 20 is mounted on gimbals 21, which are an intrinsic part of the seeker, so that the pitch 27 and yaw 28 thereof may be varied to enable sensor 20 to see or to lock onto target 12.

- 5 In the present invention, each potential target 12 is equipped with a respective flashing infra-red lamp 13 mounted thereon, which is invisible to the operator's eye but detectable by sensor 20 (CCD television camera or IIR imager). The flashing frequency is unique to each particular target 12 whereupon each lamp 13 is located.

- 10 Successive images 26 from sensor 20 are passed, at predetermined time intervals, to an image processor 22 that detects changes among images 26. The time intervals are short enough to enable image processor 26 to calculate the flash frequency of lamp 13, and, by comparison with a pre-programmed look-up table 23, to identify at which target missile 10 is 'aiming'. By comparison with data, contained in a second look-up table 24, about the shape and size of the targets, image processor 22 also determines the accuracy of aiming. This information is  
15 relayed by a wireless signal 17 to target 12, in order to detonate a pyrotechnic charge 19 situated at target 12 to simulate a 'hit' by releasing smoke 14. A second wireless signal 16 is transmitted to a training control center, in order to enable trainers to monitor and control the training program and also to rate a trainee.

In more detail, the stages of operation are:

- 20 1. Weapon simulator 10 is aimed at target 12.
2. Seeker head 11 acquires target 12 and the operator locks onto target 12. At that moment wireless transmitter 15 transmits a signal 17A to all targets and activates an infra-red lamp 13 located on each target. Each lamp 13 flashes at a unique frequency specific to the associated target thereof.
- 25 3. Simultaneously, sensor 20 passes a sequence of images 26, at predetermined time intervals, of target 12, including flashing lamp 13, to image processor 22.
4. Image processor 22 calculates the frequency of lamp 13 on acquired target 12 by comparing successive images and, by comparing the frequency with an in-built look-up table of respective target frequencies 23, identifies which target has been acquired.

5. Having thus identified target 12, image processor 22 performs a further comparison of image 26 of target 12 with target-shape data 24 stored within image processor 22 to estimate aiming precision.

6. When the trainee operator is satisfied with his aim, he 'fires' the missile, which does not actually launch. Instead, a signal 17B is sent by transmitter 15 to detonate associated pyrotechnic charge 19 located at target 12, releasing smoke 14, to simulate a 'hit'. The charge is differentially detonatable: it is possible to vary the amount of smoke in accordance with the accuracy of aim to provide a visual representation of that accuracy.

7. Information about the launcher, the target 'hit', and the accuracy of aim is transmitted to simulation control center 16 to update the data held there.

8. Preferably, the entire target-acquisition process is recorded at the control center on videotape for later debriefing.

9. The system allows for simulation of the times of flight and probability of hitting a target, for the purpose of simulation of various types of munitions (such as missile, shell, bullet, *etc*).

It is seen that the invention, by utilizing the missile's in-built sensor, solves the problem of the difference between the missile line of sight, which may vary in flight, and that of an externally attached laser, as occurs in existing systems.

Furthermore, the invention, by utilizing a passive, already in-built sensor such as a CCD camera, has advantages of weight, safety (no laser beam), operational simplicity (calibration is not needed as it would be for a separate laser system aligned with the missile), debriefing (possibility of video record), low cost (less technically complicated), and better visibility in adverse weather conditions (CCD is more sensitive than the human eye and is less affected by atmospheric conditions than lasers).

Moreover, since the present invention is normally integrated into the simulated weapon and is therefore unobtrusive, there is the consequence that a conventional laser, may be added to the simulated weapon to facilitate integration into conventional battlefield simulators that use laser or other techniques such as in the earlier mentioned BT46 system. This adds versatility to the invention.

In another embodiment, the present invention is partially realized by a simpler system, in which the image processing stage is employed without sending a signal 16 back to the control center and/or the target 12 by use of transmitter 15, which may therefore be absent.

In yet another embodiment of the present invention, wireless communication is replaced with wired transmission of signals and data. In this case, transmitter 15 is absent and is replaced by cables.

Yet another embodiment of the present invention is for non-electro-optically guided weapons systems, such as rifles and artillery. In such a ballistic implementation, wherein a gun or cannon is substituted for the launcher, there is no missile, and a sighting mechanism substitutes for the guidance system. In such cases, 'discrete portion' of the weapon includes only the gun or cannon and the sighting mechanism and 'aiming' means pointing the housing so that, if it were a real weapon, a projectile fired therefrom would follow a trajectory to the target; thus the sensor needs to be adjustable for range and other considerations in the same way as sights on a real weapon. In this embodiment, as illustrated in Figure 3, there is no signal from sensor 20 to an operator's screen and sensor 20 is not mounted on gimbals but is secured rigidly to a weapon barrel 31. An inexpensive, light-weight CCD television camera sensor is less obtrusive than a laser, as used in current systems. In this case, the aforementioned provision mentioned in stage of operation 9, for simulation of time of flight *etc* comes into play to cope with the case of ballistic projectiles, wherein the sensor points at the target while the gun barrel does not because the projectile describes a parabolic trajectory. All needed details for the simulation are calculated from positional data.

While the invention has been described with respect to a limited number of embodiments, it will be appreciated that many variations, modifications and other applications of the invention may be made.

## What is Claimed Is:

1. A simulator for simulating the firing of a weapon at one of a plurality of targets, each target having a respective shape, comprising:
  - a) a housing substantially identical in size and shape to at least a discrete portion of the weapon;
  - b) a sensor, operationally connected to said housing, for acquiring a plurality of images of at least one of the targets; and
  - c) an image processor for detecting and analyzing changes among said images and for initiating control signals based on said analysis.
2. The system of claim 1 further comprising:
  - d) for each target, an infra-red lamp that is alternatively:
    - i) activated by one of said control signals to flash at a unique, respective frequency and
    - ii) deactivated by another of said control signals; and
  - e) a mechanism for transmitting said control signals to said lamps.
3. The system of claim 2, wherein said mechanism is wireless.
4. The system of claim 2, wherein said mechanism is wired.
5. The system of claim 1 in which said sensor includes a CCD television camera.
6. The system of claim 1 in which said sensor includes part of a guidance system of an electro-optically guided missile.
7. The system of claim 1, wherein said image processor includes a look-up table that includes data about shapes of respective said targets, said image processor being operative to calculate an accuracy of an aim at the target whereat the firing of the weapon is simulated.
8. The system of claim 1 further comprising:
  - d) at each target, a pyrotechnic charge that is detonatable by a respective said control signal.
9. The system of claim 8, wherein said image processor includes a look-up table that includes data about shapes of respective said targets, said image processor being operative to calculate an accuracy of an aim at the target whereat the firing of the weapon is simulated.

10. The system of claim 9 wherein said pyrotechnic charge is differentially detonatable in accordance with said accuracy of aim calculation.

11. A method of simulating the firing of a weapon at one of a plurality of targets, comprising the steps of:

5 a) providing:

(i) a weapon simulator including a housing substantially identical in size and shape to at least a discrete portion of the weapon

(ii) a sensor, operationally connected to said housing, for acquiring a plurality of images of the target;

10 (iii) an image processor for detecting and analyzing changes among said images and for initiating control signals based on said analysis;

(iv) for each target, an infra-red lamp that is alternatively:

(A) activated by one of said control signals to flash at a unique, respective frequency and

15 (B) deactivated by another of said control signals; and

(v) a mechanism for transmitting said control signals to said lamps;

b) aiming said housing at one of the targets;

c) activating all said infra-red lamps;

20 d) acquiring a plurality of images, at predetermined time intervals, of the target whereat said housing is aimed;

e) passing said images to said image processor;

f) calculating a flash frequency of the lamp on the target whereat said housing is aimed, by comparing successive said images; and

25 g) identifying the target whereat said housing is aimed, by comparing said calculated flash frequency with a look-up table of said respective frequencies.

12. The method of claim 11, further comprising the step of:

h) visually simulating a hit.

13. The method of claim 12, wherein said simulating is effected by steps including:

i) providing, at each target, a pyrotechnic charge; and

30 ii) detonating said charge at the target whereat said housing is aimed.

14. The method of claim 13, wherein said charge is detonated differentially.

15. The method of claim 11, further comprising the step of:


h) determining an accuracy of said aim.

16. The method of claim 15, wherein said determining of said accuracy is effected by steps  
5 including:

i) providing a look-up table that includes data about shapes of the targets; and

ii) comparing said images of the target with said shape data.

17. The method of claim 15, wherein said determining of said accuracy is effected by steps  
10 including calculating a trajectory from said housing to the target whereat said housing is  
aimed.



DR. MARK FRIEDMAN LTD.  
PATENT ATTORNEYS  
SAMUELOFF BUILDING  
7 HAOMANIM STREET  
67897 TEL-AVIV ISRAEL








Figure 1 — Battlefield Simulator for EO ATMS



**Figure 2 — Schematic of Operation of  
 Seeker Head and Image Processor**



**Figure 3 — Implementation for non-EO guided weapons**